



# PERFORMANCE HAND BANDING FILM

## TECHNICAL DATA SHEET

### PRODUCT DESCRIPTION

STRANFLEX® Performance Hand Banding Film is available in narrow widths and does not require excessive force to apply, making it a user-friendly option. It can be used as an extra layer of security before applying full pallet stretch film for extra stabilization.

### APPLICATIONS

- Bundling small boxes and cartons
- Unitizing bagged or boxed products
- Retail, eCommerce, and fulfillment operations
- Light manufacturing and assembly
- Transportation, storage, and load consolidation
- Universal application across operations

### TECHNICAL DATA

ITEM #	GA	ELMENDORF TEAR STRENGTH MD	ELMENDORF TEAR STRENGTH TD	ULTIMATE TENSILE STRENGTH MD	ULTIMATE TENSILE STRENGTH TD	MAXIMUM ELONGATION MD	MAXIMUM ELONGATION TD	PROTRUSION PUNCTURE	PROTRUSION PUNCTURE ENERGY
		(ASTM D1922)		(ASTM D882)		(ASTM D882)		(ASTM D5748)	
SFP119076	47	220 g/mil	600 g/mil	1280 psi	4500 psi	300%	500%	7.3 lbs	26.0 in-lb
SFP119127	47								
SFP203076	80	365 g/mil	600 g/mil	6000 psi	2000 psi	380%	590%	9.0 lbs	18.0 in-lb
SFP203127	80								
SFP203127.1	80								

There is a +/- 10% tolerance on all the testing metrics. The data in the tables are nominal values based on PSTC, ASTM and other standard testing. The data should not be considered as specifications.

### Let's package up the right solution for your needs.

STRANFLEX packaging products are exclusively sold and distributed by BradyPLUS. Discover the full product range at STRANFLEX.com.

PKE-IND-SF0083 v1 04-2026



Exclusively available through BradyPLUS and our Regional Distribution Brands  
BradyPLUS.com + (877) 788-PLUS

© BradyPLUS