

Superior High Gloss Finish



PRODUCT ICONS

Product Category:
FLOOR FINISH



ITEM #KL-FCHFF7 (5-GALLON BAG-IN-BOX)

Hard Film, Superior Wear, Non-Scuff - Recommended for use on all types of resilient tile (vinyl composition, vinyl, linoleum) and properly sealed hard surfaces (marble, terrazzo).

PRODUCT FEATURES

- » Versatile - Works with both conventional and high speed equipment
- » Saves labor hour and money - Extends time span between stripping and recoating
- » Provides a high shine finish

PRODUCT SPECIFICATIONS

Brand	KleenLine PRO
Product Category	Floor Finish
Color	White
Fragrance	Characteristic. Slight
pH	8.1 - 8.9
Drying time	20-30 Minutes
Leveling	Excellent
Gloss	1 Coat 75-80, 2 Coat 80-85
Scuff resistant	Excellent
Relative density	1.031
Coverage	2,000 sq. ft. per gallon*
Packaging	5 Gallon
UPC barcode	810037736335

INGREDIENTS

Water (7732-18-5); Acrylic Polymer (N/A); Ethoxydiglycol (111-90-0); Tributoxyethyl Phosphate (78-51-3); Dipropylene Glycol Methyl Ether (34590-94-8).

DIRECTIONS

Recommended for use on all types of resilient tile flooring and properly prepared hard surfaces.

RESTORATIVE MAINTENANCE: Completely remove all old wax, finish and soil from floor surface following strip procedure instructions on stripper label. Floor surface must be clean, dry and free of residue before finish is applied. Rinse with clean water if necessary. Apply finish in uniform, thin to medium coats using a clean synthetic finish mop, microfiber mop or applicator system. Allow each coat to dry thoroughly before applying additional coats, usually 20 - 30 minutes. Elevated temperatures, heavy coats and humidity may extend dry time. A minimum of 4 coats of finish is recommended. Note: This product is a self-sealing finish, however, if tile is old, worn or porous, initially applying 1 - 2 coats of a sealer will enhance gloss and long term performance.

ROUTINE MAINTENANCE: Sweep large debris and dust mop. Damp mop or automatic scrub using a floor cleaner. Buff or burnish the floor to enhance gloss as needed. Use cleaner/restorer to condition the floor and extend the time between top scrub and recoating.

INTERIM MAINTENANCE: Sweep large debris and dust mop. Top scrub the floor using scrub and maroon pad or equivalent to remove the top soiled layers of finish. Floor surface must be clean, dry and free of residue before finish is applied. Apply 1 - 2 coats of finish as directed above. Please recycle empty containers. Note: Slip resistance meets or exceeds standard, (ASTM D2047-11) James Machine 0.5 minimum.

*This is typical coverage for these products. Actual coverage depends on the porosity and other characteristics of the surface being treated.

EXPERTLY DESIGNED FOR PROFESSIONALS!

KleenLine® is an exclusive BradyPLUS product line for the Facility Care market. The wide range of products enables customers to meet budget and cleaning objectives and solve all cleaning challenges from the simplest to the most complex. KleenLine® provides quality tools and solutions that are built to withstand the demands of the professional and assist with doing the job more effectively and efficiently.

SCAN FOR
SUPPORT &
RESOURCES

