

# STRAN FLEX®

## ELITE CLEAR ACRYLIC TAPE

### TECHNICAL DATA SHEET

#### PRODUCT DESCRIPTION

STRANFLEX® Elite Clear Acrylic Tape is a durable biaxially-oriented polypropylene (BOPP) film coated with high-grade pressure-sensitive water-based acrylic adhesives. Requires no moisture, heat or solvent for activation.

#### BOX WEIGHT APPLICATION

1.6: Small-Medium,  
1.8-2.5: Medium-Heavy

#### BACKING / ADHESIVE TYPE

BOPP Film / Rohm + Haas

#### ELONGATION AT BREAK

(%) ASTM D3759 >100%

#### APPLICATION RANGE

+32°F ~ +150°F

#### OPERATION RANGE

-30°F ~ +200°F

ITEM #	TAPE SIZE	BACKING THICKNESS	ADHESIVE	ADHESIVE TENSILE STRENGTH (ASTM D3759)	ADHESION TO STEEL (ASTM D3330)	TOTAL THICKNESS (ASTM D3652)	PACK					
SFE4810016A	48 mm x 100 m	0.91 mil	Emulsion Acrylic	17 lb <sub>f</sub> /in	15.65 oz/in	1.57 mil	36 rls/cs					
SFE7210016A	72 mm x 100 m						24 rls/cs					
SFE4810018A	48 mm x 100 m	0.98 mil	Acrylic	18 lb <sub>f</sub> /in	16.99 oz/in	1.77 mil	36 rls/cs					
SFE7210018A	72 mm x 100 m						24 rls/cs					
SFE4810020A	48 mm x 100 m	1.10 mil	Emulsion Acrylic	21 lb <sub>f</sub> /in	17.88 oz/in	1.97 mil	36 rls/cs					
SFE7210020A	72 mm x 100 m						24 rls/cs					
SFE4891420A	48 mm x 914 m						6 rls/cs					
SFE7291420A	72 mm x 914 m						4 rls/cs					
SFE48137120A	48 mm x 1,371 m						6 rls/cs					
SFE72137120A	72 mm x 1,371 m						4 rls/cs					
SFE4810025A	48 mm x 100 m						1.30 mil	Acrylic	25 lb <sub>f</sub> /in	21.46 oz/in	2.44 mil	36 rls/cs

The data in the table are nominal values based on PSTC, ASTM and other standard testing. The data should not be considered as specifications.

#### Let's package up the right solution for your needs.

STRANFLEX packaging products are exclusively sold and distributed by BradyPLUS. Discover the full product range at STRANFLEX.com.

PKE-IND-SF0012 v4 10-2025



Exclusively available through BradyPLUS and our Regional Distribution Brands  
BradyPLUS.com + (877) 788-PLUS

© BradyPLUS