



ELITE CLEAR HOT MELT TAPE

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

STRANFLEX® Elite Clear Hot Melt Tape is a high-performance packaging tape with aggressive hot melt adhesive for fast bonding and strong seals on corrugated surfaces. Ideal for manual and automated applications in high-speed, heavy-duty environments. Made in the USA.

BOX WEIGHT APPLICATION

1.6: Small-Medium,
1.8-2.0: Medium-Heavy

ADHESIVE / TYPE

Synthetic Rubber / Resin
Rohm + Haas

ITEM #	TAPE SIZE	BACKING THICKNESS	BACKING TYPE	ADHESIVE TENSILE STRENGTH (ASTM D3759)	ELONGATION AT BREAK (ASTM D3759)	ADHESION TO STEEL (ASTM D3330)	TOTAL THICKNESS (ASTM D3652)	APPLICATION RANGE	OPERATION RANGE	PACK
SFE4810016H	48 mm x 100 m	1.0 mil	Cast Film	23 lb _f /in	< 80%	26 oz/in	1.60 mil	+45°F ~ +120°F	-10°F ~ +140°F	36 rls/cs
SFE7210016H	72 mm x 100 m									24 rls/cs
SFE4891416H	48 mm x 914 m	1.0 mil	Cast Film	19 lb _f /in	< 110%	26 oz/in	1.60 mil	+45°F ~ +120°F	-10°F ~ +140°F	6 rls/cs
SFE7291416H	72 mm x 914 m									4 rls/cs
SFE485018H	48 mm x 50 m	1.1 mil	Blown Film	24 lb _f /in	< 80%	28 oz/in	1.85 mil	+45°F ~ +120°F	-10°F ~ +140°F	36 rls/cs
SFE4810018H	48 mm x 100 m									36 rls/cs
SFE7210018H	72 mm x 100 m									24 rls/cs



ELITE CLEAR HOT MELT TAPE

TECHNICAL DATA SHEET

ITEM #	TAPE SIZE	BACKING THICKNESS	BACKING TYPE	ADHESIVE TENSILE STRENGTH (ASTM D3759)	ELONGATION AT BREAK (ASTM D3759)	ADHESION TO STEEL (ASTM D3330)	TOTAL THICKNESS (ASTM D3652)	APPLICATION RANGE	OPERATION RANGE	PACK
SFE4891418H	48 mm x 914 m	1.1 mil	Blown Film	22 lb _f /in	< 110%	28 oz/in	1.85 mil	+45°F ~ +120°F	-10°F ~ +140°F	6 rls/cs
SFE7291418H	72 mm x 914 m									4 rls/cs
SFE48150018H	48 mm x 1,500 m									6 rls/cs
SFE72150018H	72 mm x 1,500 m									4 rls/cs
SFE48137118H	48 mm x 1,371m									6 rls/cs
SFE4810020H	48 mm x 100 m	1.1 mil	BOPP Film	27 lb _f /in	< 130%	26 oz/in	1.95 mil	+35°F ~ +120°F	-4°F ~ +140°F	36 rls/cs
SFE7210020H	72 mm x 100 m									24 rls/cs
SFE4891420H	48 mm x 914 m	1.3 mil	BOPP Film	22 lb _f /in	< 130%	26 oz/in				6 rls/cs
SFE7291420H	72 mm x 914 m									4 rls/cs

The data in the table are nominal values based on PSTC, ASTM and other standard testing. The data should not be considered as specifications.

Let's package up the right solution for your needs.

STRANFLEX packaging products are exclusively sold and distributed by BradyPLUS. Discover the full product range at [STRANFLEX.com](https://www.stranflex.com).

PKE-IND-SF0013 v3 10-2025



Exclusively available through BradyPLUS and our Regional Distribution Brands
[BradyPLUS.com](https://www.BradyPLUS.com) + (877) 788-PLUS

© BradyPLUS