

STRAN FLEX®

PERFORMANCE CLEAR ACRYLIC TAPE

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

STRANFLEX® Performance Clear Acrylic Tape is a durable biaxially-oriented polypropylene (BOPP) film coated with high-grade pressure-sensitive water-based acrylic adhesive. Requires no moisture, heat or solvent for activation.

BOX WEIGHT APPLICATION

1.6: Small, 1.8–2.0: Medium, 2.5: Heavy

BACKING / ADHESIVE TYPE

BOPP Film / Rohm + Haas

ELONGATION AT BREAK

(%) ASTM D3759 >100%

APPLICATION RANGE

+32°F ~ +150°F

OPERATION RANGE

-30°F ~ +200°F

ITEM #	TAPE SIZE	BACKING THICKNESS	ADHESIVE	ADHESIVE TENSILE STRENGTH (ASTM D3759)	ADHESION TO STEEL (ASTM D3330)	TOTAL THICKNESS (ASTM D3652)	PACK
SFP4810016A	48 mm x 100 m	1.00 mil	Water-Based Acrylic	18 lb _f /in	23 oz/in	1.6 mil	36 rls/cs
SFP7210016A	72 mm x 100 m						24 rls/cs
SFP4810018A	48 mm x 100 m	1.00 mil	Water-Based Acrylic	20 lb _f /in	23 oz/in	1.8 mil	36 rls/cs
SFP7210018A	72 mm x 100 m						24 rls/cs
SFP4810020A	48 mm x 100 m	1.16 mil	Water-Based Acrylic	23 lb _f /in	26 oz/in	2.0 mil	36 rls/cs
SFP7210020A	72 mm x 100 m						24 rls/cs
SFP4891420A	48 mm x 914 m						6 rls/cs
SFP7291420A	72 mm x 914 m						4 rls/cs
SFP48137120A	48 mm x 1,371 m						6 rls/cs
SFP72137120A	72 mm x 1,371 m						4 rls/cs
SFP4810025A	48 mm x 100 m	1.48 mil	Water-Based Acrylic	25 lb _f /in	32 oz/in	2.5 mil	36 rls/cs

The data in the table are nominal values based on PSTC, ASTM and other standard testing. The data should not be considered as specifications.

Let's package up the right solution for your needs.

STRANFLEX packaging products are exclusively sold and distributed by BradyPLUS. Discover the full product range at STRANFLEX.com.

PKE-IND-SF0014 v4 10-2025



Exclusively available through BradyPLUS and our Regional Distribution Brands
BradyPLUS.com + (877) 788-PLUS

© BradyPLUS